

STB-2810

2 Belt Side Seal with Pneumatic Head

Texwrap quality and reliability

- Compact size
- Flexible
- Big capacity
- Easy operation



The 2810 is Texwrap's offering for applications requiring the wrapping of products at moderate speed where product length or height exceeds the capacity of an L-sealer. The 2810 has a big product handling capacity capable of wrapping products up to 10' high and up to 28' wide and, with film/conveyor speeds of 100 feet per minute, the 2810 has plenty of speed to handle a variety of applications.

The 2810's 2-belt design means that the end seal is made prior to the side seal. This design allows the 2810 to fit in the space of an L-sealer but also requires the product to be spaced apart prior to entering the infeed conveyor.

The 2810 is easy to use, rugged enough for constant operation, and comes standard with premium features not available on competitive models in this price range including low-mount film cradle, touchscreen library to easily recall package setups, and automatic dwell time compensator. Allen-Bradley controls, restricted service-level menus, and AC VFD drives make the 2810 as popular with maintenance staffs as with operators.

Made in USA

Distributed by:

Features:

- Large product size capacity
- Allen-Bradley controls
- Maximum film capacity: 36 CF (72 flat with optional centerfolder)
- Built in flexibility; wrapper can run with a variety of in-feed configurations.
- Easy change-over tool-less set up
- Color touchscreen with set-up product memory & machine diagnostics
- Upstream / downstream handshaking, quick connect cable system for additional equipment
- Welded tubular construction with powder coat finish
- Internal scrap take up with film break and take up reel alarms
- Sensorless vector AC drives
- Fully guarded

Specifications:

Maximum package size: 10 H x 28 W x infinite length
(maximum dimensions cannot be combined)

Minimum package size: 5 L x 2 W (standard)
3 L x 2 W (with closing conveyor)

Conveyor width: 28

Cross seal width: 34

Cross seal drive: Pneumatic

Maximum film width: 36 centerfolded (72 flat with optional centerfolder)

Electrical requirements: 208/240 Vac, 1 phase, 18/15 amps

Air requirements: 80 PSI, 5CF

Conveyor height: 34 to 39

Maximum film speed: 100 FPM

Operator control panel: Color touch screen

